

SJE SIGNALMASTER® SPDT Control Switch

Mechanically-activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in:

- potable water
- water
- sewage applications

The SJE SignalMaster® SPDT control switch can be wired to work in either normally open or normally closed applications. It is not sensitive to rotation.

When wired as Normally Open (high level)

The control switch turns on (closes) when the switch tips slightly **above** horizontal signaling a high level, and turns off (opens) when the switch drops slightly below horizontal.

When wired as Normally Closed (low level)

The control switch turns on (closes) when the switch tips slightly **below** horizontal signaling a low level, and turns off (opens) when the switch tips slightly above horizontal.



FEATURES

- Passed NSF Standard 61 protocol by an approved Water Quality Association laboratory.
- Can be wired to work in either normally open or normally closed applications (**Single Pole, Double Throw**).
- Mechanically-activated, snap action contacts.
- High impact, corrosion resistant, polypropylene float housing.
- Not sensitive to rotation.
- Control differential of 1.5 inches (4 cm) above or below horizontal.
- Green colored cap for easy identification of SPDT control switch.
- UL Listed for use in water and sewage.
- CSA Certified.
- Three-year limited warranty.



SPECIFICATIONS

CABLE: flexible 18 gauge, 3 conductor (UL) SJOW, water-resistant (CPE)

FLOAT: 2.74 inch diameter x 4.83 inch long (7.0 x 12.3 cm) high impact, corrosion resistant, polypropylene housing for use in sewage and water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 PSI (90 kPa)

ELECTRICAL: 5 amp, 125/250 VAC, 50/60 Hz

NOTE: This switch is not recommended for controlling:

- electric loads less than 100 milliamps, 12 VAC
- non-arcing electric loads

OPTIONS

This switch is available:

- CE certified switch available upon request
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available)
- with two mounting options that allow for flexibility in installation:
 - Mounting Clamp:** for applications where the switch can be attached to a discharge pipe or similar mounting device.

Externally Weighted: for applications where the switch can be suspended from above.

SEE BACKSIDE FOR ORDERING INFORMATION.

SJE
Rhombus®

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax
email: sje@sjerhombus.com

www.sjerhombus.com

109

SJE SIGNALMASTER® SPDT Control Switch

Mechanically-activated, narrow-angle float switch designed to activate pump control panels and alarms.

ORDERING INFORMATION

Normally Open or Normally Closed

Part Number	Description	List Price	Shipping Weight
1006094	10SGMSPDTPC	\$38.94	1.20 lbs.
1006098	10SGMSPDTWE	\$46.60	2.89 lbs.
1006095	15SGMSPDTPC	\$42.41	1.61 lbs.
1006099	15SGMSPDTWE	\$50.09	3.29 lbs.
1006096	20SGMSPDTPC	\$45.93	2.01 lbs.
1006100	20SGMSPDTWE	\$53.57	3.70 lbs.
1006097	30SGMSPDTPC	\$53.57	2.82 lbs.
1006101	30SGMSPDTWE	\$61.28	4.51 lbs.

PC = Pipe Clamp WE = Weighted Externally

Can be wired to work in either pump down (normally open) or pump up (normally closed) applications.

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

Passed NSF standard 61 protocol by an approved Water Quality Association laboratory.



UL Listed for Water & Sewage



SPECIFICATIONS

CABLE: flexible 18 gauge, 3 conductor (UL) SJOW, water-resistant (CPE)

FLOAT: 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene for use in sewage and water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

ELECTRICAL: 5 amp, 125/250 VAC, 50/60 Hz

This switch is not recommended for controlling:

- electric loads less than 100 milliamps, 12 VAC
- non-arcing electric loads

OTHER INFORMATION

NORMALLY OPEN (high level) OPERATION

The control switch closes (turns on) when the float tips slightly **above** horizontal signaling a high level, and opens (turns off) when the float drops slightly **below** horizontal in potable water, water or sewage applications.

NORMALLY CLOSED (low level) OPERATION

The control switch closes (turns on) when the float tips slightly **below** horizontal signaling a low level, and opens (turns off) when the float tips slightly **above** horizontal in potable water, water or sewage applications.

OPTIONS

PACKAGING

Bagged - Standard
Boxed - Specify and add \$1.80 to list price.
Bulk - Specify and deduct 20¢ from list price.

No Mounting -

Specify and deduct 60¢ from mounting clamp list price.

ADDITIONAL CABLE

Additional cable length over 30 feet is available at 80¢ per foot (list price).



www.sjrhombus.com
 sje@sjrhombus.com

Cat Page PN 1011938N
 © SJE-Rhombus 02/13

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617